

# TECHNICAL DATA SHEET

**Road Material Stabilisers  
(Pty) Ltd**  
1986/004184/07

PO Box 84513 Greenside  
2034 Johannesburg Gauteng  
Republic of South Africa

Tel 27 (0)11 646 4982  
Factory 27 (0)11 826 1144  
Fax 27 (0)11 646 3713

E-mail info@iss2500.co.za  
Website www.iss2500.com

## WDC

DATE: 02/005/2004  
REVISED: 19/01/2005

<p><b>DESCRIPTION:</b> WDC is a non-toxic, eco-friendly synthetic liquid that is applied undiluted to areas requiring medium to long term dust suppression. WDC is also well suited for application to trafficked surfaces with loose material present.</p>		<p><b>APPLICATION RATES:</b> <b>Initial:</b> 0.15-2 l/m<sup>2</sup> (dependent on soil conditions) <b>Maintenance:</b> Light topical <i>Application rate offered as a guide only, use as directed</i></p>													
<p><b>BENEFITS:</b></p> <ul style="list-style-type: none"> <li>- Effective all year round performance unaffected by rainfall</li> <li>- Ideal for eco-sensitive areas where concerns with contamination of water and topsoil exist</li> <li>- Suitable for application to a wide variety of soil types and surfaces</li> <li>- Minimal disruption to traffic; roads do not need to be closed to traffic for application</li> <li>- Remains active after application and can be reworked</li> <li>- No specialised equipment required</li> <li>- Biodegradable and non-toxic</li> <li>- Contains no Poly Aromatic Hydrocarbons (PAH)</li> <li>- No need to remove excess loose material</li> <li>- Freezes below minus 20 °C</li> </ul>															
<p><b>PREPARATION:</b></p> <ul style="list-style-type: none"> <li>- WDC requires minimal preparation and is added undiluted to the water bowser or other application equipment</li> </ul>															
<p><b>APPLICATION:</b></p> <ul style="list-style-type: none"> <li>- The application of WDC is a surface application and should be applied using two to three passes of the bowser depending on the ability of the surface to absorb the product</li> <li>- Adjust application rate to suit the quality of the surface being treated and its ability to absorb the WDC</li> <li>- Avoid run-off and pooling</li> <li>- Rework as and when desired</li> <li>- Apply a light maintenance application when off-site material is deposited on the treated surface</li> </ul>															
<p><b>CHARACTERISTICS:</b></p> <table border="0"> <tr> <td>Appearance</td> <td>- clear water like liquid</td> </tr> <tr> <td>Specific gravity</td> <td>- 0.85 @ 25 °C</td> </tr> <tr> <td>pH</td> <td>- N/A (not an aqueous solution)</td> </tr> <tr> <td>Odour</td> <td>- slight citrus</td> </tr> <tr> <td>Solids %m/m</td> <td>- N/A</td> </tr> <tr> <td>Diluent</td> <td>- N/A</td> </tr> </table>				Appearance	- clear water like liquid	Specific gravity	- 0.85 @ 25 °C	pH	- N/A (not an aqueous solution)	Odour	- slight citrus	Solids %m/m	- N/A	Diluent	- N/A
Appearance	- clear water like liquid														
Specific gravity	- 0.85 @ 25 °C														
pH	- N/A (not an aqueous solution)														
Odour	- slight citrus														
Solids %m/m	- N/A														
Diluent	- N/A														
<p><b>HAZARDS:</b></p> <table border="0"> <tr> <td>Fire</td> <td>- non-flammable</td> </tr> <tr> <td>Explosion:</td> <td>- non-explosive</td> </tr> <tr> <td>Skin</td> <td>- mild Irritant (prolonged contact)</td> </tr> <tr> <td>Ingestion</td> <td>- not harmful</td> </tr> <tr> <td>Eyes</td> <td>- mild irritant</td> </tr> </table>		Fire	- non-flammable	Explosion:	- non-explosive	Skin	- mild Irritant (prolonged contact)	Ingestion	- not harmful	Eyes	- mild irritant	<p><b>PRECAUTIONS:</b></p> <ul style="list-style-type: none"> <li>-</li> <li>-</li> </ul> <p>Wear protective clothing for sensitive skins Do not ingest Avoid splashing</p>			
Fire	- non-flammable														
Explosion:	- non-explosive														
Skin	- mild Irritant (prolonged contact)														
Ingestion	- not harmful														
Eyes	- mild irritant														
		<p><b>FIRST AID:</b></p> <ul style="list-style-type: none"> <li>-</li> <li>-</li> </ul> <p>Rinse with water and soap* Do not induce vomiting* Flush with water for min 20 min* <i>*(Seek prompt medical advice)</i></p>													
<p><b>STORAGE:</b></p> <table border="0"> <tr> <td>Storage temperature</td> <td>- 10-60 °C</td> </tr> <tr> <td>Transport temperature</td> <td>- 10-60 °C</td> </tr> </table>		Storage temperature	- 10-60 °C	Transport temperature	- 10-60 °C	<p><b>PACKAGING / LABELLING:</b></p> <table border="0"> <tr> <td>Packed:</td> <td>- 210 litre mild steel drums</td> </tr> <tr> <td>Label:</td> <td>- including description, application, first aid and batch number</td> </tr> </table>		Packed:	- 210 litre mild steel drums	Label:	- including description, application, first aid and batch number				
Storage temperature	- 10-60 °C														
Transport temperature	- 10-60 °C														
Packed:	- 210 litre mild steel drums														
Label:	- including description, application, first aid and batch number														